


NPN General Purpose Amplifier




Features

- Epoxy meets UL-94 V-0 flammability rating
- Moisture Sensitivity Level 1
- Halogen free available upon request by adding suffix "HF"
- NPN

Mechanical Data

- **Package:** SOT-723
- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Marking:** 1AM

■Equivalent circuit



■Maximum Ratings (Ta=25°C Unless otherwise specified)

Item	Symbol	Unit	Conditions	Value
Collector-Emitter Voltage	V_{CEO}	V	$I_C=1.0mA, I_B=0$	40
Collector-Base Voltage	V_{CBO}	V	$I_C=10\mu A, I_E=0$	60
Emitter-Base Voltage	V_{EBO}	V	$I_E=10\mu A, I_C=0$	6.0
Collector Current	I_C	mA		200
Collector Power Dissipation	P_C	mW		100
Thermal Resistance Junction to Ambient	$R_{\theta JA}$	°C/W		1250
Operation Junction Temperature	T_J	°C		-55 to +150
Storage Temperature	T_{STG}	°C		-55 to +150



MMBT3904M3

■ Electrical Characteristics (Ta=25°C unless otherwise specified)

Item	Symbol	Unit	Conditions	Min	Max
Collector-Emitter Voltage	V_{CE0}	V	$I_C=1.0\text{mA}, I_B=0$	40	
Collector-Base Voltage	V_{CBO}	V	$I_C=10\mu\text{A}, I_E=0$	60	
Emitter-Base Voltage	V_{EBO}	V	$I_E=10\mu\text{A}, I_C=0$	6.0	
Collector-base Cut-off Current	I_{CBO}	nA	$V_{CB}=60\text{Vdc}$		50
Collector-emitter Cut-off Current	I_{CEX}	nA	$V_{CE}=30\text{Vdc}, V_{EB}=3\text{Vdc}$		50
DC Current Gain	h_{FE}		$I_C=0.1\text{mA}, V_{CE}=1.0\text{Vdc}$	40	
			$I_C=1.0\text{mA}, V_{CE}=1.0\text{Vdc}$	70	
			$I_C=10\text{mA}, V_{CE}=1.0\text{Vdc}$	100	300
			$I_C=50\text{mA}, V_{CE}=1.0\text{Vdc}$	60	
			$I_C=100\text{mA}, V_{CE}=1.0\text{Vdc}$	30	
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	V	$I_C=10\text{mA}, I_B=1.0\text{mA}$		0.2
			$I_C=50\text{mA}, I_B=5.0\text{mA}$		0.3
Base-Emitter Saturation Voltage	$V_{BE(sat)}$	V	$I_C=10\text{mA}, I_B=1.0\text{mA}$	0.65	0.85
			$I_C=50\text{mA}, I_B=5.0\text{mA}$		0.95
Collector-base Output Capacitance	C_{ob0}	pF	$V_{CB}=5.0\text{Vdc}, f=1.0\text{MHz}, I_E=0$		4
Transition frequency	f_T	MHz	$I_C=10\text{mA}, V_{CE}=20\text{V}, f=100\text{MHz}$	300	
Delay Time	t_d	ns	$V_{CC}=3.0\text{V}, V_{BE}=0.5\text{V}, I_C=10\text{mA}, I_{B1}=1.0\text{mA}$	35	
Rise Time	t_r	ns		35	
Storage Time	t_s	ns	$V_{CC}=3.0\text{V}, I_C=10\text{mA}, I_{B1}=I_{B2}=1.0\text{mA}$	200	
Fall Time	t_f	ns		50	

■ Ordering Information (Example)


PREFERRED P/N	PACKING CODE	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
MMBT3904M3	F2	Approximate 0.0013	8000	80000	320000	7" reel




MMBT3904M3

■ Characteristics (Typical)


Static Characteristic




DC Current Gain




Collector-Emmitter Saturation Voltage




Base-Emmitter Saturation Voltage



Base-Emmitter On Voltage




$C_{ob}/C_{ib}-V_{CB}/V_{EB}$






MMBT3904M3

■SOT-723 Package Outline Dimensions



SYMBOL	DIMENSIONS			
	INCHES		Millimeter	
	MIN.	MAX.	MIN.	MAX.
A	0.017	0.022	0.430	0.550
A1	0.000	0.002	0.000	0.050
b	0.007	0.011	0.170	0.270
b1	0.011	0.015	0.270	0.370
c	0.003	0.008	0.080	0.200
D	0.045	0.049	1.150	1.250
E	0.045	0.049	1.150	1.250
E1	0.030	0.033	0.750	0.850
e	0.031TYP.		0.800TYP.	
θ	7°REF.		7°REF.	

■SOT-723 Suggested Pad Layout



Note:

1. Package Body Sizes Exclude Mold Flash And Gate Burrs.
2. Tolerance 0.1mm Unless Otherwise Specified.
3. The Pad Layout Is For Reference Purposes Only.



MMBT3904M3

Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.